

## BOEIPLEX PRIMED



### Okoume throughout - Pre-painted panels Exterior gluing Class 3 - E1

Fascia board produced with selected Okoume veneers round and profiled edges.  
Grey or white acrylic primary paint.  
Thickness of 80 microns on each face - Edges painted.  
To be painted.



The mark of responsible forestry



## TECHNICAL INFORMATION

### DEFINITION

Semi-finished Okoume throughout plywood, covered on both sides with a grey or white layer of acrylic paint - 80 microns.

First coated on both faces with a UV mastic to block the pores followed by a primary waterbased paint, Boeiplex Primed has an ultra smooth surface which gives an excellent finish.

All that is then needed is a final coat of paint after a slight sanding.

#### Advantages:

- Considerable time saving in terms of installation, as well as labour and paint savings.

### GENERAL INFORMATION

Compliance of plywood with European norms:

- Gluing class: according to EN 314-2
- Dimension tolerance: according to EN 315

### INSTALLATION ADVICE

- An extra finish to make the sides and the edges water resistant is required.

- Slight sanding prior to application of the layer of the paint or laquer improves the surface aspect and the adherence of the final layer of paint.
- Most types of paints are compatible with acrylic paint, but we recommend testing each type of paint prior to application.
- Particular care should be taken to ensure that the edges of the panels are completely sealed.

### HANDLING RECOMMENDATIONS

Special care must be taken by handling the panel especially at the scarf joint.

### SPECIFICATIONS

Thickness: 18 mm.

CE NS marking for non-structural use (according to EN 13986).

|                            |   |
|----------------------------|---|
| Density:                   | 500 kg/m <sup>3</sup> (± 50 kg/m <sup>3</sup> ) |
| Fire reaction:             | D-s2, d0  |
| Formaldehyde emission:     | Class E1  |
| Heat conductivity:         | λ = 0,13 W/m.k                                  |
| Pentachlorophenol content: | < 5 ppm   |

| Thickness mm | Sizes cm |
|--------------|----------|
| 18           | 605 x 20 |
|              | 605 x 25 |
|              | 605 x 30 |
|              | 605 x 35 |
|              | 605 x 40 |

For FSC®-certified panels, depending on availability, contact us. - Other thicknesses and sizes upon request.