



## Pre-painted poplar throughout Gluing class 2 - E1

Poplar throughout plywood covered on both sides with a coat of 80-micron white acrylic paint - To be painted.  
Interior layout applications: furnishing, joinery, decoration.



## TECHNICAL INFORMATION

### DEFINITION

Semi-finished Poplar throughout panel, covered on both sides with a 80 micron white water-based primer paint.  
First coated on both faces with a UV mastic to block the pores followed by a primary water-based paint, Joubert Poprimed has an ultra smooth surface which gives an excellent finish.

### Advantages:

Considerable time saving in terms of installation, as well as labour and paint savings. Lightness of the panel.

### GENERAL INFORMATION

#### Compliance of plywood with European norms:

- Gluing class: according to EN 314-2
- Dimension tolerance: according to EN 315
- Panel marking: according to EN 636

### INSTALLATION ADVICE

- Slight sanding prior to application of the paint layer or laquer improves the surface aspect and the adherence of the final paint layer.

- Joubert Poprimed panels are not designed to be left as they are and require at least one paint layer to be finished. Most types of paint are compatible with acrylic paint, but we recommend testing each type of paint prior to application.
- Particular care should be taken to ensure that the edges of the panels are completely sealed.

### SPECIFICATIONS

Thicknesses: 9 to 22 mm.

**CE2+** marking for structural use according to EN 13986 (control certificate delivered by FCBA).

|                            |   |
|----------------------------|---|
| Density:                   | 450 kg/m <sup>3</sup> (± 50 kg/m <sup>3</sup> ) |
| Fire reaction:             | D-s2, d0*                                       |
| Formaldehyde emission:     | Class E1<br>US EPA TSCA Title VI - CARB ULEF    |
| Heat conductivity:         | λ = 0,11 W/m.k                                  |
| Pentachlorophenol content: | < 5 ppm   |

\* Depending on how the panel is installed.

| Thickness mm | Sizes cm  |
|--------------|-----------|
| 9            | 250 x 122 |
| 10           |           |
| 12           |           |
| 15           |           |
| 18           |           |
| 22           |           |

For PEFC-certified panels, depending on available credits, contact us.