

## JOUBERT PRIMED GARANT

Okoume throughout - Pre-painted panels  
Exterior gluing Class 3 - E1  
NF Extérieur CTB-X certified (for structural use)

White acrylic primary paint.  
Thickness of 80 microns on each face - To be painted.  
Eaves fascia, soffits, exterior cladding.



## TECHNICAL INFORMATION

### DEFINITION

Semi-finished Okoume throughout plywood, covered on both sides with a white layer of acrylic paint - 80 microns. First coated on both faces with a UV mastic to block the pores followed by a primary water-based paint, Joubert Primed has an ultra smooth surface which gives an excellent finish.

All that is then needed is a final coat of paint after a slight sanding.

#### Advantages:

Considerable time saving in terms of installation, as well as labour and paint savings.

### GENERAL INFORMATION

#### Compliance of plywood with European norms:

- Gluing class: according to EN 314-2
- Dimension tolerance: according to EN 315
- Panel marking: according to EN 636

### INSTALLATION ADVICE

- Slight sanding prior to application of the layer of the paint or laquer improves the surface aspect and the adherence of the final layer of paint.
- Most types of paints are compatible with acrylic paint, but we recommend testing each type of paint prior to application.
- Particular care should be taken to ensure that the edges of the panels are completely sealed.

### SPECIFICATIONS

Thicknesses: 8 to 40 mm.

☑☑2+ marking for structural use according to EN 13986 (control certificate delivered by FCBA).

Density:	500 kg/m <sup>3</sup> (± 50 kg/m <sup>3</sup> )
Fire reaction:	D-s2, d0 for thicknesses ≥ 10 mm* E for thicknesses < 10 mm*
Formaldehyde emission:	Class E1 US EPA TSCA Title VI - CARB ULEF
Heat conductivity:	λ = 0,13 W/m.k
Pentachlorophenol content:	< 5 ppm

\* Depending on how the panel is installed.

**JOUBERT PRIMED GARANT****TECHNICAL INFORMATION**

Thickness mm	Sizes cm
<b>8</b>	<b>250 x 122</b>
<b>10</b>	<b>310 x 122</b>
<b>12</b>	<b>310 x 153</b>
<b>15</b>	<b>215 x 95</b>
<b>18</b>	<b>235 x 95</b>
<b>20</b>	<b>235 x 105</b>
<b>22</b>	
<b>25</b>	
<b>30</b>	
<b>35</b>	
<b>40</b>	

For FSC®-certified panels, depending on availability, contact us.