

PUBLIGRAPH

Selected Okoume

Smooth white 205 g/m² melamine film on 2 faces

Exterior gluing Class 3 - E1

NF Extérieur CTB-X certified (for structural use)

Smooth and glossy melamine film 205 g/m² on both sides.
Silk-screen printing, advertising boards, road signs, rear truck doors, industrial refinishing, signs.



TECHNICAL INFORMATION

DEFINITION

Top of the range Okoume throughout plywood with selected veneers, coated on both sides with a smooth white 205 g/m² film ideal for silk-screen printing in exterior use.

The film does not require any particular protection and it is mainly intended for the manufacturing of advertisement boards, signs and for fittings in industrial coachbuilding both inside and outside.

GENERAL INFORMATION

Compliance of plywood with European norms:

- Gluing class: according to EN 314-2
- Dimension tolerance: according to EN 315
- Panel marking: according to EN 636

INSTALLATION ADVICE

The edges, which are not protected, must be made waterproof.

Thickness mm	Sizes cm
10	250 x 122
12	310 x 153
15	
18	

For FSC®-certified panels, depending on availability, contact us.

SPECIFICATIONS

Thicknesses: 10 to 18 mm.

☞2+ marking for structural use according to EN 13986 (control certificate delivered by FCBA).

Density:	500 kg/m ³ (± 50 kg/m ³)
Fire reaction:	D-s2, d0*
Formaldehyde emission:	Class E1 US EPA TSCA Title VI - CARB ULEF
Heat conductivity:	λ = 0,13 W/m.k
Pentachlorophenol content:	< 5 ppm

* Depending on how the panel is installed.