



STARK

Igaganga face veneers II/III
Okoume/Igaganga cores
Exterior gluing Class 3 - E1
NF Exterior CTB-X certified

Stark plywood panels are made from Igaganga hardwoods for outdoor use. Thanks to their strength and stability, they are suitable for a wide range of uses in the transport, furniture, fittings and construction industries.



TECHNICAL INFORMATION

GENERAL INFORMATION

Compliance of plywood with European norms:

- Gluing class: according to EN 314-2
- Faces classification: according to EN 635-2
- Dimension tolerance: according to EN 315
- Panel marking: according to EN 636

SPECIFICATIONS

Thicknesses: 5 to 25 mm.

CE NS marking for non-structural use (according to EN 13986)

Density:	600 kg/m ³ (± 50 kg/m ³)
Fire reaction:	D-s2, d0
Fire resistance:	1,3 mm/mn
Heat conductivity:	λ = 0,15 W/m.k
Pentachlorophenol content:	< 5 ppm

Thickness mm	Number of plies	Sheets per pack	250 x 122 cm
5	3	50	✓
8	5	62	✓
10	5	50	✓
12	7	42	✓
15	7	33	✓
18	9	28	✓
22	11	23	✓
25	11	20	✓

For FSC®-certified panels, depending on availability, contact us.

* Information on the level of emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a class scale from A+ (very low emissions) to C (high emissions).