



STARTPLEX

Okoume face veneers II/III
Exterior gluing Class 3 - E1
NF Extérieur CTB-X certified (for structural use)

Okoume faced twin panel for non exposed outdoor use.
 Common outdoor applications without any direct or prolonged exposure (many applications on work sites).



TECHNICAL INFORMATION

GENERAL INFORMATION

Compliance of plywood with European norms:

- Gluing class: according to EN 314-2
- Faces classification: according to EN 635-2
- Dimension tolerance: according to EN 315
- Panel marking: according to EN 636-3

SPECIFICATIONS

Thicknesses: 5 to 40 mm.

CE2+ marking for structural use (according to EN 13986) for panels with a thickness ≥ 8 mm (control certificate delivered by FCBA).

CE NS marking for non-structural use (according to EN 13986) for panels with a thickness < 8 mm.

Density:	475 kg/m ³ (± 50 kg/m ³)
Fire reaction:	D-s2, d0 for thicknesses ≥ 10 mm* E for thicknesses < 10 mm*
Formaldehyde emission:	Class E1 US EPA TSCA Title VI - CARB ULEF
Heat conductivity:	$\lambda = 0,13$ W/m.k
Pentachlorophenol content:	< 5 ppm

* Depending on how the panel is installed.

Thickness mm	Sizes cm
5	250 x 122
8	310 x 153
10	
12	
15	
18	
20	
22	
25	
30	
40	

For PEFC-certified panels, depending on available credits, contact us.