

DECLARATION OF PERFORMANCE

DoP n°VAPB - Thickness : 22 mm

1. PLYWOOD FOR HUMID CONDITIONS EN 636-2 S.
2. Product : JOUBERT POPRIMED - Thickness : 22 mm
3. Intended use as STRUCTURAL COMPONENTS
4. Manufactured by JOUBERT Les Eliots - rue des Epinées - Les Eliots - 16170 Auge Saint-Médard - France and JOUBERT Saint-Jean d'Angély - rue Lafaurie - 17400 Saint-Jean d'Angély - France
6. Systems of Assessment and Verification of Constancy of Performance : 2+
7. Notified body FCBA 0380 performed the initial inspection of the manufacturing plants and of factory production controls and the continuous surveillance, assessment and evaluation of factory production controls and issued the certificates of conformity of factory production controls.
9. Declared performance :

Essential characteristics	Performance	Harmonised technical specification
Bonding quality	Class 2	EN 13986 : 2004
Reaction to fire	D-s2, d0	
Water vapour permeability μ - wet	70	
- dry	200	
Release of formaldehyde	E1	
Release of pentachlorophenol	PCP \leq 5 ppm	
Airborne sound insulation	NPD	
Sound absorption	NPD	
Thermal conductivity	$\lambda = 0,12 \text{ W/(m.K)}$	
Air permeability	NPD	
Biological durability	Use Class 2	
Bending Strength	NPD	
Bending Stiffness	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturers identified in point 4.

Signed of and on behalf of the manufacturers by Thierry JOUBERT, Manager of the Board of Directors Auge Saint-Médard, 14 March 2014

Thierry JOUBERT